


DS-A30-I HAMMER

- ***IR3.5/XL3 SHANK DESIGN***
- ***NEW GENERATION***
- ***SUPERIOR TECHNOLOGY***
- ***STANDARD BIT DIAMETERS: 3.5 - 4***
- ***DELIVERS MORE ENERGY PER BLOW***
- ***HARDENED PISTON FOR EXTENDED LIFE***
- ***INNOVATIVE DESIGN FOR MAXIMUM PERFORMANCE WITH MINIMUM MAINTENANCE***

The newest generation of Drilling Supply Hammers means faster penetration, longer life, and less down time due to down hole failures.



No.	Descripción	Qty
1	WEAR SLEEVE	1
2	TOP SUB	1
3	TOP SUB O-RING	1
5	SPACER RING	1
6	MAKE UP RING	1
7	CK VALVE	1
8	CHOKE	1
9	CK VALVE SPRING	1
10	AIR DISTRIBUTOR	1
11	AIR DIS. O-RING	1
12	CYLINDER	1
14	PISTON	1
17	PISTON RET. RING	1
18	BIT RET. RING	1
19	BIT RET. RING O-RING	1
20	BEARING	1
22	CHUCK	1

Drilling Parameters

Air Consumption at Different Working Pressures

Dimensions and Weights

Working Pressure	150-350	150 psi	215 (scfm)	Top Sub	2-38" API PIN
				Tool Length (in)	34.25
Application Bit	3.5"-4"	200 psi	275 (scfm)	Outside Dia. (in)	3.35
				Piston Diameter (in)	2.40
Feed Force (lbs.)	500-1,900	250 psi	350 (scfm)	Stroke (in)	3.00
		350 psi	480 (scfm)	Weight w/o bit (lbs)	53
				Piston Weight (lbs)	8.4